



BT-WHITE
Matt
Satin
Anti-slip



BT-CUARCITA
Textured stone effect
base tile

Standard tile sizes

- 316 x 637 x 9 mm (14" x 25")
- 491 x 491 x 9 mm (19" x 19")
- 491 x 982 x 9 mm (19" x 39")

Custom sizes also available, please enquire

Weight per sq metre: approx 15 kg

Finishes Available: Textured Stone effect, Matt, Anti-slip, Satin

Made to order: 6-8 weeks

Field Tiles available

These products have been certified in accordance with ISO quality standards by independent authorised laboratories. Maintenance free, they are extremely durable, easy to clean and have anti-slip, non-combustible and knock-resistant characteristics.

TECHNICAL INFORMATION (Abridged)

Product Type	Porcelain / Quartzite floor and wall tiles	
Finishes and Suitability		
Finishes Available	Textured stone effect, Matt, Anti-slip, Satin	
Suitability	Interior/Exterior use for floors (also suitable for walls and cladding)	
Areas of Use - Product Suitability		
Domestic	Kitchens, bathrooms, conservatories, etc	YES
Residential	Hotels, Housing, etc	YES
Public Areas/High traffic	Restaurants, offices, shops, pavements, etc	YES

		TEST STANDARDS
Resistance to slip	= $R_d = 65$ (Class 3) (top rating)	UNE-ENV1 2633 ISO/DIS 10545-17
Resistance to Surface Abrasion All Colours: PEI Rating	= 4	EN ISO 10545-07
Surface Hardness All Colours: MoHs rating	= 6 (Conforms)	EN 101
Water Absorption All colours: Conforms (acc to test criteria)		EN ISO 10545-03
Acid & Alkali Resistance All colours: Results GLC (Acids, Alkalis) (Conforms) All colours: Results GB (Household) (Conforms)		EN ISO 10545-13
Frost Resistance All Colours: Resistant (acc to test criteria) (Conforms)		EN ISO 10545-12
Impact resistance by measurement of coefficient of restitution (Conforms)		EN ISO 10545-5
Thermal Expansion	= $6.4 \times 10^{-6}/^{\circ}C$ (Conforms)	EN ISO 10545-8

COLLECTIONS

DESIGN

WWW.CRINSON.COM

BESPOKE
PHOTOGRAPHIC
DESIGN

WWW.DIGITILE.CO.UK