



**Standard tile sizes**

310 x 632 x 9 mm (12" x 24")  
 388 x 388 x 9 mm (15" x 15")  
 491 x 982 x 9 mm (19" x 19")  
 Custom sizes also available, please enquire

**Weight per sq metre:** approx 18 kg

**Made to order:** 7 weeks

These products have been certified in accordance with ISO quality standards by independent authorised laboratories. Maintenance free, they are extremely durable, easy to clean and have anti-slip, non-combustible and knock-resistant characteristics.

TECHNICAL INFORMATION (Abridged)

<b>Product Type</b>	Porcelain / Quartzite floor and wall tiles	
<b>Finishes and Suitability</b>		
<b>Finishes Available</b>	Textured stone effect, Matt, Anti-slip, Satin. Polished finish available on 388x388	
<b>Suitability</b>	Interior/Exterior use for floors, walls and cladding.	
<b>Areas of Use - Product Suitability</b>		
<b>Domestic</b>	Kitchens, bathrooms, conservatories, etc	YES
<b>Residential</b>	Hotels, Housing, etc	YES
<b>Public Areas/High traffic</b>	Restaurants, offices, shops, pavements, etc	YES

		TEST STANDARDS
<b>Resistance to slip</b>	= <b>R<sub>d</sub> = 65 (Class 3)</b> (top rating)	<b>UNE-ENV1 2633</b> <b>ISO/DIS 10545-17</b>
<b>Resistance to Surface Abrasion</b> All Colours: PEI Rating	= 4	<b>EN ISO 10545-07</b>
<b>Surface Hardness</b> All Colours: MoHs rating	= 6 (Conforms)	<b>EN 101</b>
<b>Water Absorption</b> All colours: Conforms (acc to test criteria)		<b>EN ISO 10545-03</b>
<b>Acid &amp; Alkali Resistance</b> All colours: Results GLC (Acids, Alkalis) (Conforms) All colours: Results GB (Household) (Conforms)		<b>EN ISO 10545-13</b>
<b>Frost Resistance</b> All Colours: Resistant (acc to test criteria) (Conforms)		<b>EN ISO 10545-12</b>
<b>Impact resistance by measurement of coefficient of restitution</b> (Conforms)		<b>EN ISO 10545-5</b>
<b>Thermal Expansion</b>	= 6.4*10 <sup>-6</sup> /°C (Conforms)	<b>EN ISO 10545-8</b>

COLLECTIONS

DESIGN

**WWW.CRINSON.COM**

BESPOKE  
PHOTOGRAPHIC  
DESIGN

**WWW.DIGITILE.CO.UK**